

## DIN TYPE (EUROPEAN)



CAPACITY Ah	EN -18°C	MF&SMF	Color	L x W x H mm	Warranty	Layout
60	540	MF/SMF	Black	240x175x190	18	0/1
62	620	MF/SMF	Black	240x175x190	18	0/1
75	740	MF/SMF	Black	278x175x190	18	0/1
80	780	MF/SMF	Black	278x175x190	18	0/1
100	870	MF/SMF	Black	353x175x190	18	0/1
110	900	MF/SMF	Black	353x175x190	18	0/1

## HEAVY DUTY



CAPACITY AH	EN -18°C	MF&SMF	Color	L x W x H mm	Warranty month	Layout
140	1000	MF/SMF	Black	512x188x215	12	3/4
145	1050	MF/SMF	Black	512x188x215	12	3/4
190	1200	MF/SMF	Black	512x220x215	12	3/4
192	1250	MF/SMF	Black	512x220x215	12	3/4
225	1350	MF/SMF	Black	518x275x237	12	3/4
230	1400	MF/SMF	Black	518x275x237	12	3/4

## JIS TYPE (JAPANESE)

CAPACITY Ah	EN -18°C	MF&SMF	Color	L x W x H mm	Warranty month	Layout
60	600	MF/SMF	Grey	235x178x220	18	0/1
72	750	MF/SMF	Grey	260x173x220	18	0/1
100	850	MF/SMF	Grey	304x173x224	18	0/1

0		Length	Terminal	A (Standart)	B (Small)	Stud	Dual
				Positive			
1		Length	Negative				
						3/8"-16 Thread	
3		Length	B1			B13	5 notches 10.5mm on all four sides
				10.5mm on long sides only	10.5		
4		Length	B3			B14	3 notches 21mm
				Base hold down 10.5 mm (on long and short sides)	10.5		
18		Length					